

Water Coolers Standard Series

Consistency in performance, competitive pricing & one piece blow-molded cabinet of high-density polyethylene with UV resistance additives make this cooler a popular long-life rental unit.

Model:

Standard H/C (Hot and Cold)

Standard C/C (Cook and Cold)

Standard EZ H/C (Hot and Cold)

Standard EZ C/C (Cook and Cold)

Standard POU H/C (Hot and Cold)

Standard POU C/C (Cook and Cold)

- Graceful design, easy to maintain and convenient to use
- Food grade stainless steel (SUS304) hot tank and cooling tank
- Large and durable drip tray
- High quality and efficient compressor for reliable and consistent performance
- Available in White and Black color
- 2 years limited warranty



Standard Series are
Energy Star rated



POU



Standard Series

Technical Data & Specifications



Cabinet & Chassis: One piece blow molded high-density polyethylene plastic. Resists cracking, fading and yellowing. Color molded in to hide scrapes caused by rough usage. Easily removed for access to interior components. The shock absorbing base is of ABS plastic and will never rust.

Cold Water Refrigeration Unit: Convection cooled condenser. Internal, spring mounted, hermetically sealed compressor with automatic overload protector. No lubrication needed. Refrigerant is controlled accurately by a capillary tube.

Cold Water Thermostat: Temperature is controlled by an adjustable thermostat with "OFF" position that is easily accessible on the rear of the unit.

Cold Water Reservoir: Food grade stainless steel type SUS304, 1 gallon (3.8 liter) reservoir. Provides superior chilling for great tasting water. Highly polished surface is easy to clean and maintain.

Hot Water Tank: Food grade stainless steel type SUS304, 0.32 gallon (1.2 liter) capacity. The 520 watts heating element ensures precise temperature control. Removable thermostat and heating element ease service.

Electrical:
Cooler operates on 115 volts, 60 Hertz
Refrigerant:
All units contain HFC-134a refrigerant.

Shipping Dimension

Height	39.0 in. (990mm)
Width	12.8 in. (325mm)
Depth	13.2 in. (335mm)

Shipping Weights

Cook & Cold	33.1 lbs. (15kg)
Hot & Cold	35.3 lbs. (16kg)

Cooler Dimension

Height	37.0 in. (940mm)
Width	12.2 in. (310mm)
Depth	12.6 in. (320mm)

Cooler Weights

Cook & Cold	30.9 lbs. (14kg)
Hot & Cold	33.1 lbs. (15kg)



Standard Series are Energy Star rated



Cooling and Heating Capacities Room Temperature	°F (°C)	70° (21°)	80° (27°)	90° (32°)
Quality for cold water Served per hour	GPH LPH	1.2 4.5	0.9 3.2	0.5 1.9
Number of 3oz. (89ml.) Cups of 50°F (10°C) water Served per hour		53	38	22
Hot water deliver at 180°F (82°C) [for Hot & Cold model only]		45 cups of 6oz. (178ml.) per hour		

Specifications are subject to change without notice. Bottle & Filter System not included with cooler.
IGO Consolidated Corporation Sdn. Bhd.

1, Jalan SS 19/4E, 47500, Subang Jaya, Selangor Darul Ehsan. Malaysia. • www.igocon.com • +603-31766668 • Fax +603-31764600